

# Technical Data Sheet

## 1,6-Hexanediol

| Chemical Name      | 1,6-Hexanediol  |
|--------------------|-----------------|
| CAS #              | 629-11-8        |
| Formula            | C6H14O2         |
| Molecular Weight   | 118.17          |
| Synonyms           | HEXANE-1,6-DIOL |
| Chemical Structure | но              |

### Description

HDO is a linear, bifunctional, primary alcohol. It is a white waxy solid at room temperature and a clear liquid at temperatures above its melting range.

| •    | •           |
|------|-------------|
| 38-4 | 42          |
| 250  | )           |
| 0.96 | 3           |
| 137  | ,           |
|      | 250<br>0.96 |

### Specification

| Item                       | Specification |
|----------------------------|---------------|
| Assay, % min.              | 99.5          |
| Water, % max.              | 0.07          |
| Solidification Temperature | 42.8          |
| Acid Number, koll/g        | 0.01          |
| Chromaticity (Hazen60@c)   | 10            |
| Every Other Impurity       | Confirms      |
| Total Impurities, %        | 0.30          |

Hefei TNJ Chemical Industry Co.,Ltd.

B911 Xincheng Business Center, Qianshan Rd. Hefei 230022 China Tel : (0086) 551 65418695 Fax: (0086) 551 65418697 Email: info@tnjchem.com Site: www.tnjchem.com

#### Applications

1,6-Hexanediol is a valuable intermediate product for the chemical industry. It finds application in a variety of polymeric systems and is also used in the synthesis of specialty chemicals. This linear diol contains two primary hydroxyl groups which are terminally located. This configuration results in a rapid and simultaneous reaction in the formation of numerous di-substituted products.

As a solvent, 1,6-Hexanediol can be used in/with

- Microcellular polyurethane
- Cast elastomers
- Fibers
- Adhesives
- Plasticizers
- Dyestuffs
- Cosmetics
- Insecticides
- Surfactants
- Printing inks

#### Packaging

| Waxy solid:                     | Flak |
|---------------------------------|------|
| 200kg per plastic or iron drum. | 25k  |
| 16tons(80drum)/20"FCL           | 13te |

Flake: 25kg per pp woven bag 13tons(520bags)/20"FCL

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchant ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if we has been advised of the possibility of such damages.

#### Hefei TNJ Chemical Industry Co.,Ltd.

Qianshan Road, Hefei 230022 Anhui China Fax:(0086) 551 65418697Email:info@tnjchem.comSite:www.tnjchem.com